

PS - 15-22



PS 15:22

Solid mounted Washer

Washing machine low speed extraction with very robust construction.

Capacity 15 kg/filling, with dual motor system. Perfect washing result ideal for kindergartens hotels and similar institutes.

Very easy mechanical programmer and temperature thermostat control of the machine.

Long life machine that needs bolting down to the floor. Top load soap dispenser with 3 compartments with big capacity for detergents.

The housing of the machine and inner and outer drum and all other parts of the machine that come in contact with water are made of stainless steel material (quality AISI 304), possibility of cooldown system for very delicate linen, (this avoids "thermic shocks" on the linen) easily accesible to maintenance works. (all panels of housing can be removed very easily)

Fast and efficient heating water system.

Krebe - Tippo d.o.o., Italia :: Via Bertoloni 59 :: 54036 M. di Carrara :: Italy
 :: krebe.italia@email.it :: www.krebe-tippo.si Tel +39 0585 851114 - 0585 851679 Fax +39 0585 855892



TYPE OF MACHINE			PS-15	PS-22
CAPACITY	1:10	kg/filled	15	22
SIZE OF THE DRUM	diameter	mm	620	620
	depth	mm	510	650
ROTATION SPEED	wash speed	rot/min	43	43
high spin speed		rot/min	420	420
G - FACTOR			61	61
POWER OF THE ELECTRO ENGINE		kW	0,25/1,1	0,25/1,1
HEATING POWER (MPa)	steam 0.8	kW	43	43
	steam 0.05	kW	43	43
electrical 400V, 3N AC, 50 Hz		kW	dec.18	18
SIZE OF THE MACHINE	width	mm	810	810
	depth	mm	850	990
	height	mm	1250	1250
NET WEIGHT OF THE MACHINE	net	kg	230	260

E - electrical heating
 Pv - high pressure steam heating
 Pn - low pressure steam heating
 K - combined heating (Pv + E)